

# HBL-STD-TB50

Tazze | Cleats



## specifiche tazza | cleat specifications

|                | um   | norme   norms | valore   value |
|----------------|------|---------------|----------------|
| peso   weight  | kg/m |               | 2,2            |
| colore   color |      |               | nero   black   |

## specifiche mescola | compound specifications

|                                              | um     | norme   norms | valore   value |
|----------------------------------------------|--------|---------------|----------------|
| polimero base   base polymer                 |        |               | NR/SBR         |
| durezza   hardness                           | SH/A   | ISO 7619-1    | 70             |
| peso specifico   specific weight             | g/cm^3 | ISO 2781      | 1,2            |
| carico di rottura   tensile strength         | N/mm^2 | ISO 37-1      | 12             |
| allungamento a rottura   elongation at break | %      | ISO 37-1      | 203            |
| perdita abrasione   abrasion loss            | mm^3   | ISO 4649      | 207            |
| composta da   Made of                        |        |               | P37B           |

## Tabella tolleranze | table tolerances

|                                    | da | a | Um   | tolleranza   tolerance |
|------------------------------------|----|---|------|------------------------|
| Durezza                            | -  | - | SH/A | ±5                     |
| Spessore                           | -  | - | mm   | ±0.02                  |
| resa elastica   rebound resistance | -  | - | %    | ±3                     |
| dimensioni   dimensions            | -  | - |      | ISO 3302-1-M3          |



valid from 23/12/2025

